Ref. No.: IISc/AE/Tender/2021/Global /NdYAG Date: 10th December 2021

Global tender notification for the procurement of a pulsed Nd: YAG laser (Last Date for Submission: 3rd January 2022)

GTE Approval No. IISc-GTE-2021-106

This is a Request for quote (RFQ) for procurement of a pulsed Nd:YAG laser at the department of Aerospace Engineering, Indian Institute of Science, Bangalore. The tender should be submitted in two separate sealed envelopes: one containing the technical bid and the other containing the commercial bid, both of which should reach us, duly signed on or before 5 PM on 3rd January 2022.

The bids should be addressed to:

The Chairman,
Department of Aerospace Engineering
Indian Institute of Science
Bangalore 560012, India.
Kind attention: Dr. Irfan Mulla

email: irfanmulla@iisc.ac.in, chair.aero@iisc.ac.in

1	Section 1	Bid Schedule	As specified by IISc		
2	Section 2	Eligibility Criteria	As specified by IISc		
3	Section 3	Specifications	Technical specifications		
4	Section 4	Terms and Conditions	As specified by IISc		
5	Section 5	Technical bid	Annexure 1: Bidder details		
			Annexure 2: Declaration regarding experience of		
			bidder		
			Annexure 3: Declaration regarding track		
			record of bidder		
			Annexure 4: Declaration of acceptance of Terms and		
			conditions		
			Annexure 5: Details of item quoted		
6	Section 6	Commercial bid	Quotation with Price, Technical specifications of the		
			Equipment		

Section 1: Bid Schedule

1.	Tender No	IISc/AE/Tender/2021/Global/NdYAG
2.	Tender date	10 th December 2021
3.	Instrument	A pulsed Nd:YAG laser
4.	Tender type	i) Technical bid (Part A)ii) Commercial bid (Part B)
5.	Place of tender submission	The Chairman, Department of Aerospace Engineering Indian Institute of Science Bangalore 560012, India. Kind attention: Dr. Irfan Mulla
6.	Last date and time of tender submission	3 rd January 2022, 5 PM
7.	Contact for further clarification	Dr. Irfan Mulla Department of Aerospace Engineering Indian Institute of Science Bangalore 560012, India. Ph: +91-80-2293-2875 email: irfanmulla@iisc.ac.in

Section 2: Eligibility Criteria

Prequalification criteria:

- 1. The original equipment manufacturers (OEM) firm should have existence for a minimum of 5 years (Enclose Company Registration Certificate).
- 2. The Bidder should have at least 3 years of experience in supplying and servicing pulsed Nd:YAG lasers in India.
- 3. The Bidder should have qualified technical service personnel based in India.
- 4. If the Bidder is a local Distributor/Dealer/Agent, it is mandatory to attach the authorization certificate along with the technical bid from the OEM.
- 5. The Bidder should sign and submit the declaration for Acceptance of Terms and Conditions as per Annexure 4.
- 6. The Bidder must not be blacklisted/banned/suspended or have a record of any service-related dispute with any organization in India or elsewhere. A declaration to this effect has to be given as per Annexure 3.

Section 3: Technical Specification for a pulsed Nd:YAG laser Submit quote for one pulsed Nd:YAG laser with following specifications.

T1. Mandatory specifications:

S.N.	Parameter (unit)	Specification	
1.	Pulse repetition rate (Hz)	10	
2.	Adjustable pulse repetition rates (Hz)	0 – 10 Hz (F/1 n (n = integer)). E.g., 1, 2.5, 3.33, 5, 10 Hz	
3.	Fundamental laser wavelength (nm)	1064	
4.	Laser cavity design	As described below	
4a.		Nd:YAG active medium that is flash lamp pumped	
4b.		Nd:YAG rod should be removable for ease of servicing	
4c.		Oscillator should be of single Nd: YAG rod design.	
4d.		Oscillator should have ceramic reflectors for long life.	
5.	Energy per pulse (mJ)	As described below	
5a.		≥ 850 @ 1064 nm	
5b.		≥ 425 @ 532 nm	
5c.		≥ 225 @ 355 nm	
5d.		≥ 100 @ 266 nm	
6.	Pulse duration (ns)	3 to 9 @ 1064 nm	
7.	Beam diameter (mm)	8 to 10	
8.	Beam divergence (mrad), full angle at 1/e ² of the peak	≤ 0.5 @ 1064 nm	
10.	Spatial beam profile @ 1064 nm (fit to gaussian)	As described below	
10a.		> 0.7 for near field	
10b.		> 0.9 for far field	
11.	Polarization ratio (%)	> 80 @ 1064 nm	
12.	Pulse to pulse energy stability (%). Peak to peak value for 100% of the shots [and RMS based value]	As described below	
12a.		≤± 2.5 [0.8] @ 1064 nm	
12b.		≤±4 [1.3] @ 532 nm	
12c.		≤±6 [2] @ 355 nm	
12d.	-	≤ ± 8 [2.6] @ 266 nm	
13.	Power drift (%) over 8 hours without any readjustment, considering	As described below	

	ambient temperature fluctuate between 18°C to 28°C			
13a.		≤±3 @ 1064 nm		
13b.		≤± 5 @ 532 nm		
13c.		≤±5 @ 355 nm		
13d.		≤± 10 @ 266 nm		
14a.	Pointing stability, full angle value at all harmonics (µrad)	≤ 40 @ 1064 nm, 532 nm, 355 nm, 266 nm		
15.	Jitter with respect to Q-switch trigger input (ns)	\leq ± 0.5		
16.	Linewidth (cm ⁻¹) measured at FWHM	≤ 1 @ 1064 nm		
17.	Flash Lamp lifetime of a single unit (million shots)	≥ 80		
18.	Power input	220-240 VAC, 50 Hz, single phase		
19a.	Chiller option Integrated within the power supply un laser without any need of external chil			
19b.	Internal coolant	Distilled/Deionised water		
20.	Operating temperature	18 to 28°C		
21.	Storage temperature	20 to 45°C		
22.	Sync-In signal: External trigger input to the laser	5V TTL for both Q-switch and Flash lamp		
23.	Sync-Out signal: External trigger output from the laser	5V TTL for both Q-switch and Flash lamp. TTL pulse should be standard positive going (i.e., rising edge).		

T2. Mandatory requirements/features:

- 1. Laser should have interlock feature to prevent laser damage (e.g., from high laser rod temperature or failure of coolant flow) and for safety of the user (e.g., when laser cover is removed).
- 2. Provide near-field and far-field beam profiles.
- 3. Provide second, third and fourth harmonic generators, including the wavelength separation units.
- 4. All harmonic generators should be able to attach/detach easily with minor optical adjustment.
- 5. Adjustable delay (by using internal delay generator) of the Q-Switch output synchronization signal of 5V TTL pulse with respect to opening of the Q-Switch is required to synchronize the laser with other equipment. TTL pulse adjustable delay range should at least be -500 to +500 ns with 1 ns step.
- 6. Product warranty:
 - a. At least 1 year for flashlamp.
 - b. At least 2 years for the remaining system, including optics, opto-mechanics, and electronics, but excluding the DI cartridge.
- 7. User should be able to change the flash lamp without any requirement of cavity optics realignment.
- 8. It should be possible to control the output energy by varying the delay between the flash lamp and Q-Switch and not just by adjusting the flash lamp voltage.

- 9. Detachable pump chamber and rod assembly for easy serviceability.
- 10. Installation and user training should be provided by the manufacturer or their authorized distributor.
- 11. Servicing/repair timeframe: If need arises, local servicing/repairs should be attended in three to five business days. If laser needs to be shipped abroad, repairs should be carried out preferably within ten to fifteen business days, excluding the shipping duration.

T3. Optional requirements/features:

- 1. All harmonic generators should have a motorized/automated tuning control.
- 2. All harmonic generators should have electronic temperature stabilization for better energy stability with hands free automatic phase-matching capability.
- 3. Beam quality M^2 value, at $1/e^2$ of the peak should be ≤ 2 @ 1064 nm.
- 4. Include a typical procedure employed to deduce the beam pointing stability.
- 5. Laser should have a user selectable control through RS 232/Ethernet and handheld remote control.
- 6. Quick connect electrical cable and coolant lines with at least 3 m length. Cables and coolant lines should be able to disconnect from both the power supply side and the optical head side to facilitate easy transportation.
- 7. Laser warmup feature: There should be an inbuilt heating coil to reduce warm up time as well as to keep the temperature stability of the cavity even in standby mode (when flashlamp is off).
- 8. Harmonic generators and Installations:
 - a. Direct mechanical coupling between the fundamental module and harmonic generator.
 - b. The insertion and removal of harmonic generators should be user friendly and without the requirement of any optical realignment.
 - c. There should be only one crystal per harmonic module.
 - d. All modules should have externally accessible dichroic mirror assembly and residual beam dump.
 - e. One should be able to achieve the following beam combination from all harmonic modules easily without the requirement of opening the harmonic modules.
 - i. Just the main harmonic beam
 - ii. Main harmonic beam and residual through different ports
 - iii. Main harmonic beam and residual beam from a single port co-axially.

A diagram representing the beam accessibility should be provided by the vendor.

9. Harmonic phase matching:

- a. Should be fully automatic and hands free. System should be able to do phase matching by its own after the user gives a command from the remote controller/computer.
- b. The automatic tuning / phase matching should preferably be achieved by changing the temperature of the crystal and not by changing the angle of the crystal, for better reproducibility.
- c. All harmonic modules should have the above feature with an option to monitor the relative peak energy in the remote control.
- 10. Manufacturer should provide necessary software to control the laser from a computer.
- 11. Future upgradation possibilities: Injection seeding of the laser to reduce the laser pulse linewidth to ≤ 0.005 cm⁻¹ @ 1064 nm. This upgrade should be made possible at the user laboratory without any need of shipping the laser to manufacturer.

Section 4: Terms and Conditions

- 1. All documentations in the tender should be in English.
- 2. Tender should be submitted in two envelopes (two bid system).
 - a) Technical Bid (Part-A) Technical bid consisting of all technical details and checklist for conformance to technical specifications. The proposal should contain a compliance table. The compliance table should include all the items of the technical specifications in the same order and format. The first additional column should describe product specifications. The next column should indicate compliance in a "Yes" or "No" response.
 - b) Commercial Bid (Part-B) Indicating item-wise price for the items mentioned in the technical bid, as per the format of quotation provided in tender, and other commercial terms and conditions.
- 3. The technical bid and price bid should each be placed in separate sealed covers, superscribing on both the envelopes the tender no. and the due date. Both these sealed covers are to be placed in a bigger cover which should also be sealed and duly superscribed with the Tender No, Tender Description & Due Date.
- 4. The SEALED COVER superscribing tender number and due date & should reach the office of the Chairman, Department of Aerospace Engineering Indian Institute of Science Bangalore 560012, India. Kind attention: Dr. Irfan Mulla, on or before the due date mentioned in the tender notice. In case the due date happens to be a holiday, the tender will be accepted and opened on the next working day. If the quotation cover is not sealed, it will be rejected.
- 5. The lead-time for the delivery of the equipment should be less than 6 months from the date of receipt of the purchase order. It should be clearly mentioned in the technical and commercial bids.
- 6. The vendor must provide a compliance statement in a tabular form concerning each technical specification in the tender document duly supported by the manufacturer's literature and published papers. Any other claim will not be accepted and may lead to the rejection of the bid.
- 7. Wherever requested, data must be supplied along with technical compliance documents. Technical bids without supporting data will be deemed as technically non-compliant.
- 8. The institute reserves the right to verify the accuracy and seek clarification of submitted specifications after opening the technical bids. Based on such clarification, if specifications are found to be unsuitable, the technical committee reserves the right to disqualify vendors. Any discrepancy between the promised and verified specifications will be deemed as technical noncompliance.
- 9. The technical bid should also contain warranty details and terms. Further, any periodic maintenance requirements for regular operation should be specified in detail, along with the extent of coverage under warranty for such maintenance activity.
- 10. The bidder will provide the prerequisite installation requirement of the equipment along with the technical bid. The vendor is responsible for the installation of the system at the institute, along with the training of end-users.
- 11. In the commercial bid, the price should be inclusive of all discounts (CIF Bangalore, applicable Custom Duty will be borne by the Institute). The price quotation should include the cost of installation and training of potential users if any. Please quote the price of each optional item, separately.
- 12. Any statutory increase in the taxes and duties subsequent to the bidder's offer, if it takes place within the original contractual delivery date, will be borne by IISc, Bangalore, subject to the claim being supported by documentary evidence. However, if any decrease takes place, the

- advantage will have to be passed on to IISc, Bangalore. Any information furnished by the bidder found to be incorrect, either immediately or at a later date, would render the bidder liable to be debarred from the bidding process.
- 13. The vendor should have an office with qualified technical service personnel based in India and should assure a response time of less than five business days.
- 14. The vendor must submit a list of all Indian customers (only Government of India organizations) where similar systems have been installed. References from this list can be used to disqualify vendors with a poor track record of service, build quality, system performance, or poor availability of spares. Additionally, IISc shall have the absolute right to take the opinion of other departments/institutes for their opinion/experience about the bidder's services/sales. Based on such input, IISc may decide about the rejection of a bid of such bidder(s).
- 15. The vendor shall include up to five testimonials from existing users of a similar laser system indicating the performance of the laser and maintenance satisfaction.
- 16. Notwithstanding anything specified in this tender document, IISc Bangalore, in its sole discretion, unconditionally and without having to assign any reason, reserves the rights:
 - a) To accept OR reject the lowest tender or any other tender or all the tenders.
 - b) To accept any tender in full or in part.
 - c) To reject the tender, offer not confirming the tender terms.
- 17. The indenter reserves the right to relax any or all the above conditions without assigning any reason.

Annexure 1:

Details of the Bidder: The bidder must provide the following mandatory information & attach supporting documents wherever mentioned:

Sr. No.	Туре	Details
1.	Name of the Bidder	
2.	Nature of Bidder (Attach attested copy of Certificate of Incorporation/	
3.	Deed) Registration No/ Trade	
	License, (attach attested copy)	
4.	Registered Office Address	
5.	Address for communication	
6.	Contact person- Name and Designation	
7.	Telephone No	
8.	Email ID	
9.	Website	
10.	PAN No. (attach copy)	
11.	GST No. (attach copy)	

(Signature of the Bidder)	
Name:	Date:
Designation, Seal	

Annexure 2:
Declaration regarding experience
To,
The Chairman, Department of Aerospace Engineering Indian Institute of Science Bangalore 560012, India. Kind attention: Dr. Irfan Mulla
Ref: Tender No:
Dated:
Sub: Supply and installation of a pulsed Nd:YAG laser
I have carefully gone through the Terms & Conditions contained in the above referred tender. I hereby declare that my company / firm has years of experience in supplying and installing a pulsed Nd:YAG laser.

(Signature of the Bidder) Name:

Designation, Seal

Date:

Annexure 3:

Declaration of track record

To,
The Chairman,
Department of Aerospace Engineering
Indian Institute of Science
Bangalore 560012, India.
Kind attention: Dr. Irfan Mulla

Ref: Tender No:

Dated:

Sub: Supply and installation of a pulsed Nd:YAG laser

Sir,

I have carefully gone through the Terms & Conditions contained in the above referred tender.

I hereby declare that my company / firm is not currently debarred / blacklisted by any Government / Semi-Government organizations / institutions in India or abroad. I further certify that I am competent officer in my company / firm to make this declaration.

OR

I declare the following:

Sr. No.	Country in which the	Blacklisted / debarred	Reason	Time Period
	company is debarred/	by Government / Semi		
	blacklisted / having	Government		
	pending case	Organizations or		
		Institutions / having		
		pending case		

(Note: In case the company / firm was blacklisted previously, please provide the details regarding period for which the company / firm was blacklisted and the reason/s for the same).

(Signature of the Bidder)	
Name:	Date:
Designation, Seal	

Annexure 4:

Declaration of acceptance of terms and conditions

To,
The Chairman,
Department of Aerospace Engineering
Indian Institute of Science
Bangalore 560012, India.
Kind attention: Dr. Irfan Mulla

Ref: Tender No:

Dated:

Sub: Supply and installation of a pulsed Nd:YAG laser

Sir,

I have carefully gone through the Terms & Conditions contained in the above referred tender document. I declare that all the provisions of this tender document are acceptable to my company. I further certify that I am an authorized signatory of my company and am, therefore, competent to make this declaration.

(Signature of the Bidder)
Name: Date:
Designation, Seal

Annexure 5:

Details of items quoted:

- a. Company Name
- b. Product Name
- c. Part / Catalogue number
- d. Product description / main features
- e. Detailed technical specifications
- f. Remarks, if applicable

Instructions to bidders:

- 1. Bidder should provide technical specifications of the quoted product/s in detail.
- 2. Bidder should attach product brochures along with technical bid.
- 3. Bidders should clearly indicate compliance or non-compliance of the technical specifications provided in the tender document.

Section 5 – Commercial Bid

The commercial bid should be furnished with all requirements of the tender with supporting documents as mentioned under:

Items requested in the mandatory specification section

S.No	Description	Cat. Number	Quantity	Unit Price	Sub total
1.	Essential items noted in				
	the technical specification				
2	(details of essential				
	items)				
3.	Warranty (years)				
4.	FOR-IISc Bangalore only				

Items requested in the optional specification section

S.No	Description	Cat. Number	Quantity	Unit Price	Sub total
1.	Optional items noted in				
	the technical specification				
2	(details of Optional				
	items)				
3.	Warranty (years)				
4.	FOR-IISc Bangalore only				

Section 6 - Checklist

The following items must be checked before the bid is submitted.

- 1. Sealed Envelope "A": Technical Bid
 - Technical bid (signed by the authorized signatory and sealed) with the below documents:
 - a. Annexure 1: Bidders details
 - b. Annexure 2: Declaration regarding experience
 - c. Annexure 3: Declaration of track record
 - d. Annexure 4: Declaration of acceptance of terms and conditions
 - e. Annexure 5: Details of item quoted
 - f. Authorization certificate from the OEM
- 2. Sealed Envelope "B": Commercial Bid

Your quotation must be submitted in two separate sealed envelopes: Technical Bid (Envelope A) and Commercial Bid (Envelope B) super scribing on both the envelopes with Tender No. and due date. These envelopes should be put in a bigger cover which should also be sealed and duly superscribed with Tender No., Tender description & Due Date.